

VA.03 / QC AC-VERTICAL BINDER 03

2/12/2019

PRODUCT DESCRIPTION

VA.03 / QC AC-VERTICAL BINDER 03 / QC AC-VERTICAL BINDER 03 is high-viscosity, single component co-polymer acrylate dispersion. This thixotropic transparent and low yellowing synthetic material is intended for use as a binding product to cover plinths or vertical sections of stairs with decorative quartz stone.

APPLICATION

If desired, it is possible to cover plinths and vertical sections of stairs with decorative gravel. All areas to be screeded must be primed with VA.03 / QC AC-VERTICAL BINDER 03. Mix the dry stone with 18% VA.03 / QC AC-VERTICAL BINDER 03 untill homogenous and thoroughly wetted out. Apply this to the wet vertical section with a stainless trowel. Once dry (appr.24 hours) the horizontal sections can be screeded . Effective ventilation will quicken the curing time

ATTENTION

Not possible with the sm-colours!

If you want to seal the plinths or vertical sections afterwards, the VA.03 / QC AC-VERTICAL BINDER 03 must be fully cured out (duration at least 3 days).

VA.03 / QC AC-VERTICAL BINDER 03 is only possible for inside use

PROPERTIES

	VA.03 / QC AC-VERTICAL BINDER 03
Easy to apply	
PH value	8 – 9
MFT	4°C
Colour	milky mayonnaise-like paste that forms a fully transparent clear film when dry
Density	1.02 at 20°C
Viscosity	thixotropic paste
Usage	± 18% on dry ground
Cleaning of equipment	water
Storage	In a cool, dry, damp-proof space,
Storage	Can be stored for minimum 6 – 12 months when in sealed packaging.
Packaging	buckets of 10 kg or upon request
Drying	trafficable after 24 hours Almost fully hardened after 7 days 100% hardening after 28 days

SAFETY

Read always the material safety datasheet of the product.

