

APR / AC-LIGHT DUTY PRIMER

01/09/2011

PRODUCT DESCRIPTION

APR / AC-LIGHT DUTY PRIMER is a low viscosity, 1- component acrylate copolymer dispersion. This transparent substance is used to bind dusty bases (cement, plaster, wood...) and to rid them of dust.

APPLICATION

Can be used before implementing floor or wall systems. For floors, one must ensure that an acrylate film is not present on the floor, and full penetration into the base is recommended in order to prevent a reduction in bonding in the floor system.

PROPERTIES

	APR / AC-LIGHT DUTY PRIMER
Colour	milky
Density at 20°C	± 1,02 kg/dm ³
Viscosity	± 50 mPa.s
Ignition point	n/a
Drying at 20°C and 65% RV	treadable: after 30 minutes
overschilderbaar:	after 1 hour
Processing temperature	4°C - 30°C
Requirements for base	- sufficiently dry - free of loose particles, grease, dirt,...
	- water-tight - sufficiently tolerant to pressure / stretching
Dilution	ready to use
Cleaning	water
Usage	depending on porosity of base
Packaging	buckets or tins of 10 kg or upon request
Storage	12 months (in sealed, original packaging, 10-25°C)

IMPLEMENTATION

Mix before use and apply with a roller or brush. Ensure sufficient ventilation so that the product can dry. It's also possible to sprinkle the primer with fire-dried quartz (0.1-0.3 or 0.4-0.8).

SAFETY

Read always the material safety datasheet of the product.

