

Technical sheet

MARBLE

Application area

Sidec decorative marble can be used in all kinds of applications such as: marble carpet, Terradec, decorative applications,...

Contact Sidec for application on other types of substrates.



Properties

Marble is a metamorphosed limestone, consisting of very pure calcium carbonate with a relative hardness of 3 Mohs. Sidec marble consists of washed, dried and rounded marble grains. To ensure quality and minimize dust or excess, the marble is sieved very carefully. Due to the natural origin of these granules, slight color variations may occur.

Technical data

Hardness:	3 Mohs
Form :	Mechanically rounded
	Grain size 4-8 mm
	Grain size 1-4 mm
PH Value:	7,0 ± 0,5
Packaging :	In 25 kg PE bags. On request, we can also deliver in big bags.
Conservation :	Unlimited stockage, provided if it is kept dry and protected from light

Colours

Arabescato / Bardiglio light / Bardiglio / Botticino / Breccia aurora / Breccia pernice / Carnico / Carrara / Giallo siena / Grigio carnico / Grigio cenere / Madagascar / Marrone / Nero ebano / Niagara blue / Occhialino / Rosa corallo / Rouge royal / Royal brown / Verde alpi / Zandobbio

Safety measures

Read the safety sheets carefully before using EP-Rapid Primer. Always wear personal protective equipment according to the applicable local guidelines and legislation. Gloves and safety glasses are mandatory.

Technical support

Sidec nv
Industrieweg 10
2490 Balen - België
Tel. + 32 14 81 50 01
sales@sidec.be